

Dane techniczne łyżki przesiewające oraz kruszące

| Model      | Maszyna bazowa |           | Przepływ oleju | Ciśnienie | Pojemność | Wymiary   |         |                        |          | Waga | Granulacja |           |           |
|------------|----------------|-----------|----------------|-----------|-----------|-----------|---------|------------------------|----------|------|------------|-----------|-----------|
|            | Koparka        | Ładowarka |                |           |           | Min - Max | ISO/SEA | Powierzchnia przesiewu | Wysokość |      |            | Szerokość | Głębokość |
|            |                |           |                |           |           | l/min     |         | m <sup>2</sup>         |          |      |            |           |           |
| VPH 3-950  | 7              | 2         | 60-120         | 200/300   | 0.45/0.53 | 0.6       | 1000    | 1250                   | 1200     | 630  | 16, 24, 35 |           |           |
| VPH 3-1500 | 9              | 4         | 60-250         | 200/300   | 0.70/0.80 | 1.0       | 1000    | 1750                   | 1200     | 890  | 16, 24, 35 |           |           |
| VPH 4-1500 | 12             | 5         | 110-250        | 200/300   | 1.00/1.10 | 1.3       | 1200    | 1750                   | 1200     | 1300 | 16, 24, 35 |           |           |
| VPH 3-1700 | 21             | 10        | 120-250        | 200/350   | 2.30/2.50 | 1.4       | 1400    | 2050                   | 2100     | 2250 | 18, 25, 35 |           |           |
| VPH 4-1700 | 24             | 12        | 120-250        | 200/350   | 2.80/3.10 | 1.55      | 1550    | 2050                   | 2250     | 2600 | 18, 25, 35 |           |           |
| VPH 3-2300 | 35             | 18        | 170-250        | 200/350   | 3.50/4.10 | 2.0       | 1800    | 2600                   | 2200     | 2800 | 18, 25, 35 |           |           |
| VPV 4-1100 | 14             | xx        | 120-250        | 200/350   | 1.00/1.20 | 0.9       | 1500    | 1300                   | 1300     | 1350 | 18, 25, 35 |           |           |
| VPV 5-1350 | 16             | xx        | 120-250        | 200/350   | 1.30/1.50 | 1.15      | 1500    | 1550                   | 1300     | 1650 | 18, 25, 35 |           |           |
| VPH 4-2300 | 30             | 21        | 170-250        | 200-350   | 3.90/4.50 | 2.4       | 1400    | 2650                   | 1800     | 3200 | 18, 25, 35 |           |           |
| VPH 2-1500 | 7              | 4         | 60             | 200       | 0.65/0.75 | 0.6       | 950     | 1700                   | 1050     | 480  | 0-28 mm    |           |           |
| VPCH - 21  | 22             | xx        | 250-440        | 330-350   | 0,95/1.30 | x         | 1350    | 1500                   | 1800     | 2300 | 40-150 mm  |           |           |
| VPCV - 22  | 25             | xx        | 250-440        | 330-350   | 1.50/1.70 | x         | 1450    | 1750                   | 1550     | 2900 | 40-150 mm  |           |           |

KONTAKT:

Konrad Sas tel: 608 208 445

e-mail: wendor@wendor.pl

www.wendor.pl